Bike, What Bike! Classic Bike BOUND INSERT SPECIFICATIONS

DELIVER TO:

BGP Ltd, Chaucer Business Park, Launton Road, Bicester, OX26 4QZ

Book in delivery of inserts with **Naomi O'Sullivan 01869 363345**– Failure to book in deliveries may result in them being turned away

PRESENTATION AND PACKAGING:

Inserts should be on non-returnable, pallets capable of being double stacked Pallets must be 4-way entry; 1,200mm x 1,000mm & be in good condition Pallet banding must be plastic to comply with Health & Safety requirements Metal banding will result in refusal of the delivery Containers and metal cages are also unacceptable Pallets should be wrapped to provide stability and weather protection of inserts If cartons are necessary, the maximum weight is 25kg per package Labels must state publication name, month and quantity of inserts / box or pallet Inserts should be stacked in large bundle quantities, not less than 50 per turn Inserts in cartons must be unbanded and not turned within the box Inserts must be packed flat with tight folds, no distortions or any curled edges Inserts in cartons must display a sample and a suitable label on the outside Inserts must not be shrinkwrapped

Failure to comply could result in additional costs being incurred

MINIMUM & MAXIMUM SIZES FOR INSERTS TO BE MECHANICALLY INSERTED

MINIMUM WIDTH (spine to foredge): 140mm MAXIMUM WIDTH: 223mm (INC TRIMS)

MINIMUM DEPTH: (head to foot) 140mm MAXIMUM DEPTH: 310mm (INC TRIMS)


MINIMUM WEIGHT 115gsm (single leaf)

ALLOWANCES TO BE MADE

Spine (mill off)- The mill off allowance is 3mm. This is the amount of paper that will be taken off before gluing the covers.

Head Trim – 5mm (assuming it will knock to the head)

Foot Trim – 3 – 10mm (where applicable) **Foredge Trim** – 3-10mm (where applicable)



NO INSERTS OF LANDSCAPE ORIENTATION PERFORATED INSERTS MUST HAVE A 13MM PERF WIDTH FROM SPINE.

FOR FURTHER INFORMATION ON INSERTS CONTACT PRINT PRODUCTION ON 01733 468062